AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1-17. (cancelled)

- 18. (currently amended) A hanger for a dosimeter with a virtual opening for providing a window of practically unrestricted by absorption passage to radiation, the hanger consisting of a polymeric material, and housing having a base and a cover and being adapted to receive a dosimeter, the window being an integral part of the surrounding portion of the hanger formed as one-piece with the housing and having a reduced thickness with respect to the housing that is less than or equal 0.1 mm.
- 19. (original) The housing of claim 18, wherein the window has a thickness of at least $0.02\ \mathrm{mm}$.
- 20. (currently amended) The housing of claim 18, consisting of wherein the housing is one piece.
- 21. (original) The housing of claim 18, wherein the window has a thickness of about 0.07 mm to 0.08 mm.
- 22. (original) The housing of claim 18, wherein the window has a thickness of at least 0.03 mm.
 - 23. (new) A hanger for a dosimeter, comprising: a base; and

Docket No. 5010-1009 Appln. No. 10/798,953

a cover pivotally attached to said base and formed as one-piece with said base,

one of said base and said cover having an area of reduce thickness forming a virtual opening for providing a window of practically unrestricted by absorption passage to radiation,

said base and cover being a molded polymeric material, and

said window having a thickness less than or equal 0.1 mm.

- 24. (new) The hanger of claim 23, wherein the window has a thickness of between 0.1 mm and 0.02 mm.
- $25. \ (\text{new})$ The hanger of claim 23, wherein the window has a thickness of about 0.07 mm to 0.08 mm.
- 26. (new) The hanger of claim 23, wherein the window has a thickness between $0.1\ mm$ and $0.03\ mm$.
- 27. (new) The hanger of claim 23, comprising only one window.
- 28. (new) The hanger of claim 23, wherein said base and cover each include a flange extending from a respective one of said base and cover and forming a corresponding recess.
- 29. (new) The hanger of claim 28, further comprising positioning element on said base and a mating positioning element on said cover.
- 30. (new) The hanger of claim 29, further comprising a lip extending perpendicular to said flange for creating a

Docket No. 5010-1009 Appln. No. 10/798,953

moisture-proof seal when said base and cover are in a closed position.